

TABELLE ROHRAUSSENDURCHMESSER

Nennweite DN	DIN DIN 11850	ISO EN ISO 1127	Zoll ASME	DA (mm)	DA (inch)
				3,17	0.125
				6,00	0.236
			1/4"	6,35	0.250
	6			8,00	0.315
			3/8"	9,53	0.375
	8			10,00	0.394
		10,2		10,20	0.402
				12,00	0.472
			1/2"	12,70	0.500
	10			13,00	0.512
8		13,5		13,50	0.531
				15,88	0.625
				16,00	0.630
10		17,2		17,20	0.677
				18,00	0.709
	15			19,00	0.748
			3/4"	19,05	0.750
				20,00	0.787
15		21,3		21,30	0.839
				22,00	0.866
	20			23,00	0.906
			1"	25,40	1.000
20		26,9		26,90	1.059
				28,00	1.102
	25			29,00	1.142
				30,00	1.181
25		33,7		33,70	1.327
	32			35,00	1.378
			1 1/2"	38,10	1.500
				40,00	1.575
	40			41,00	1.614
32		42,4		42,40	1.669
				44,50	1.752
40		48,3		48,30	1.902
			2"	50,80	2.000
				51,00	2.008
				52,00	2.047
	50			53,00	2.087
				54,00	2.126
50		60,3		60,30	2.374
			2 1/2"	63,50	2.500
	65			70,00	2.756
65		76,1		76,10	2.996
			3"	76,20	3.000
	80			85,00	3.346
80		88,9		88,90	3.500
			4"	101,60	4.000
	100			104,00	4.094
				108,00	4.252
100		114,3		114,30	4.500
			5"	127,00	5.000
	125			129,00	5.079

125		139,7		139,70	5.500
			6"	152,40	6.000
	150			154,00	6.063
				165,10	6.500
150		168,3		168,30	6.626
				177,80	7.000
				190,50	7.500
	200			204,00	8.031
200		219,1		219,10	8.626

Lagermäßig geführte Spannbacken für OSK-Schweißköpfe:



Sonderabmessungen auf Anfrage